



Reference: 810-145

### Max / Min Therma-Hygrometer

Therma-hygrometer with dual LCD screen that simultaneously displays temperature and humidity readings displayed and recorded maximum and minimum. A rear folding stand and slot allow placement in both flat surfaces and walls.

#### STANDARD PARAMETERS

Sensor element (Temperature / Humidity): Thermistor / Capacitor  
 Measuring range (Temp. / Hum.): 0 to 50°C / 10 to 99%rh  
 Scale (Temp. / Hum.): Celsius-Fahrenheit (°C/F) / Relative humidity  
 Resolution (Temp. / Hum.): 0.1°C / 1%  
 Accuracy (Temp. / Hum.): ±1°C / ±5%  
 Battery: 1x1.5 volts AAA  
 Battery life: 10.000 hours  
 Dimensions: 20x100x110mm  
 Weight: 135g

#### MATERIALS

Housing: ABS plastic Display: LCD Dual

#### Application:

- Control
- Storage
- Greenhouse
- Domestic use



\*Temperature only calibration

### Max / Min Therma-Hygrometer with external probe

Therma-hygrometer with dual LCD screen that simultaneously displays temperature and humidity readings displayed and recorded maximum and minimum. It also includes an external 3m cable probe. A rear folding stand and slot allow placement in both flat surfaces and walls



Reference: 810-140

#### STANDARD PARAMETERS

Sensor element (Temperature / Humidity): Thermistor / Capacitor  
 Measuring range internal sensor: 0 to 50°C  
 Measuring range external probe (Temp. / Hum.): -20 to 70°C / 10 to 99%rh  
 Scale (Temp. / Hum.): Celsius-Fahrenheit (°C/F) / Relative humidity  
 Resolution (Temp. / Hum.): 0.1°C / 1%  
 Accuracy (Temp. / Hum.): ±1°C / ±5%  
 Battery: 1x1.5 volts AAA  
 Battery life: 10.000 hours  
 Dimensions: 20x100x110mm  
 Weight: 170g

#### MATERIALS

Housing: ABS plastic Display: LCD Dual

#### Application:

- Control
- Storage
- Cold chambers
- Greenhouse
- Domestic use



\*Temperature only calibration

### Therma-Hygrometer with Max / Min & alarm functions

Therma-hygrometer with dual LCD displays the current indoor temperature and humidity. It records minimum and maximum that can activate the audible alarm. It also incorporates a foldable stand for flat surfaces and a slot for hanging on the wall. The alarm is activated when the external probe temperature goes under 0°C, this feature is ideal to warn of freeze danger in sectors such as horticulture and the like. Each unit is supplied with a probe with a 3-meter PVC wire that can be mounted onto any wall using the suction pad



Reference: 810-155

#### STANDARD PARAMETERS

Sensor element (Temperature / Humidity): Thermistor / Capacitor  
 Measuring range internal sensor: 0 to 49.9°C  
 Measuring range external probe (Temp. / Hum.): -49.9 to 69.9°C / 20 to 99%rh  
 Scale (Temp. / Hum.): Celsius-Fahrenheit (°C/F) / Relative humidity  
 Resolution (Temp. / Hum.): 0.1°C / 1%  
 Accuracy (Temp. / Hum.): ±1°C / ±5%  
 Battery: 1x1.5 volts AAA  
 Battery life: 10.000 hours  
 Dimensions: 20x65x97mm  
 Weight: 78g

#### MATERIALS

Housing: ABS plastic Display: LCD Dual

#### Application:

- Control
- Storage
- Cold chambers
- Greenhouse
- Domestic use



\*Temperature only calibration